



# Caledonian

Airport Flame Retardant And Fire Resistant Cables



www.caledonian-cables.com

marketing@caledonian-cables.com

## 600/1000V XLPE Insulated, LSZH Sheathed, Armoured Power Cables (Single Core)

FTX300 1RZ1MZ1-R 1G300 (CU/XLPE/LSZH/AWA/LSZH 600/1000V Class 2)

Indoor Feeder Cables



### APPLICATIONS

This cables are mainly used in power stations, mass transit underground passenger systems, airports, petrochemical plants, hotels, hospitals, and high-rise buildings.

### STANDARDS

Basic design to BS 6724

### FIRE PERFORMANCE

Flame Retardance (Single Vertical Wire Test)	EN 60332-1-2; IEC 60332-1-2; BS EN 60332-1-2; VDE 0482-332-1 ; NBN C 30-004 (cat. F1); NF C32-070-2.1(C2); CEI 20-35/1-2; EN 50265-2-1*; DIN VDE 0482-265-2-1*
Reduced Fire Propagation (Vertically-mounted bundled wires& cable test)	EN 60332-3-24 (cat. C); IEC 60332-3-24; BS EN 60332-3-24; VDE 0482-332-3; NBN C 30-004 (cat. F2); NF C32-070-2.2(C1); CEI 20-22/3-4; EN 50266-2-4*; DIN VDE 0482-266-2-4
Halogen Free	IEC 60754-1; EN 50267-2-1; DIN VDE 0482-267-2-1; CEI 20-37/2-1 ; BS 6425-1*
No Corrosive Gas Emission	IEC 60754-2; EN 50267-2-2; DIN VDE 0482-267-2-2; CEI 20-37/2-2 ; BS 6425-2*
Minimum Smoke Emission	IEC 61034-1&2; EN 61034 -1&2; DIN VDE 0482-1034-1&2; CEI 20-37/3-1&2; EN 50268-1&2*; BS 7622-1&2*
No Toxic Gases	NES 02-713; NF C 20-454

### VOLTAGE RATING

600/1000V

### CABLE CONSTRUCTION

Conductor : Plain annealed copper wire, stranded according to IEC 60228 class 2.

Insulation: Extruded cross-linked XLPE compound.





# Caledonian

## Airport Flame Retardant And Fire Resistant Cables

[www.caledonian-cables.com](http://www.caledonian-cables.com)

[marketing@caledonian-cables.com](mailto:marketing@caledonian-cables.com)

300	0.155	r:0.17 x:0.175 z:0.25	r:0.145 x:0.15 z:0.21	r:0.17 x:0.22 z:0.28	0.37	0.24	0.32	0.21
-----	-------	--------------------------	--------------------------	-------------------------	------	------	------	------




Rated voltage



BS 6724



Flame Retardant  
NF C32-070-2, IEC2  
IEC60332-1-3, EN50265-2-1



Halogen Free  
IEC 60754-1



Low Corrosivity  
IEC60754-2, EN50267-2-2, 3  
NF C32-074, NF C20-453



Low Smoke Emission  
IEC 61034-2 / EN 50268-2  
NF C32-073, NF C 20-962



Low Toxicity  
NES 02-713, NF C 20-454



Reduced Fire Propagation  
NF C32-070-2, 2(C1)  
IEC60332-3-24, EN50266-2-4