



Caledonian

Airport Flame Retardant And Fire Resistant Cables



www.caledonian-cables.com

marketing@caledonian-cables.com

600/1000V XLPE Insulated, LSZH Sheathed, Armoured Power Cables (4+1 Cores)

FTX400 1RZ1MZ1-R 4G120/50 (CU/XLPE/LSZH/SWA/LSZH 600/1000V Class 2)

Indoor Feeder Cables (from MDB to SDB, SDB to TDB) & UPS Feeder Cables



APPLICATIONS

This cables are mainly used in power stations, mass transit underground passenger systems, airports, petrochemical plants, hotels, hospitals, and high-rise buildings.

STANDARDS

Basic design to BS 6724

FIRE PERFORMANCE

Flame Retardance (Single Vertical Wire Test)	EN 60332-1-2; IEC 60332-1-2; BS EN 60332-1-2; VDE 0482-332-1 ; NBN C 30-004 (cat. F1); NF C32-070-2.1(C2); CEI 20-35/1-2; EN 50265-2-1*; DIN VDE 0482-265-2-1*
Reduced Fire Propagation (Vertically-mounted bundled wires& cable test)	EN 60332-3-24 (cat. C); IEC 60332-3-24; BS EN 60332-3-24; VDE 0482-332-3; NBN C 30-004 (cat. F2); NF C32-070-2.2(C1); CEI 20-22/3-4; EN 50266-2-4*; DIN VDE 0482-266-2-4
Halogen Free	IEC 60754-1; EN 50267-2-1; DIN VDE 0482-267-2-1; CEI 20-37/2-1 ; BS 6425-1*
No Corrosive Gas Emission	IEC 60754-2; EN 50267-2-2; DIN VDE 0482-267-2-2; CEI 20-37/2-2 ; BS 6425-2*
Minimum Smoke Emission	IEC 61034-1&2; EN 61034 -1&2; DIN VDE 0482-1034-1&2; CEI 20-37/3-1&2; EN 50268-1&2*; BS 7622-1&2*
No Toxic Gases	NES 02-713; NF C 20-454

VOLTAGE RATING

600/1000V

CABLE CONSTRUCTION

Conductor: Plain annealed copper wire, stranded according to IEC 60228 class 2

Insulation: Extruded cross-linked XLPE compound



Caledonian

Airport Flame Retardant And Fire Resistant Cables

www.caledonian-cables.com

marketing@caledonian-cables.com

120	0.39	r:0.4 x:0.145 z:0.42	r:0.34 x:0.13 z:0.37	0.42	0.42	0.36	0.36
-----	------	-------------------------	-------------------------	------	------	------	------



Rated voltage



BS 6724



Flame Retardant
NF C32-070-2, IEC2
IEC60332-1-3, EN50265-2-1



Halogen Free
IEC 60754-1



Low Corrosivity
IEC60754-2, EN50267-2-2/3
NF C32-074, NF C20-453



Low Smoke Emission
IEC 61034-2 / EN 50268-2
NF C32-073, NF C 20-962



Low Toxicity
NES 02-713, NF C 20-454



Reduced Fire Propagation
NF C32-070-2, 2(C1)
IEC60332-3-24, EN50266-2-4