



# Caledonian



BS 6346 Cables

www.caledonian-cables.com

marketing@caledonian-cables.com

## BS 6346 PVC Insulated Cables, 1900/3300V

Single-core 1900/3300V cables with circular stranded copper conductor  
1C400



### APPLICATIONS

These cables are used for power and control circuits, they can offer excellent protection through the use of a heavy galvanized steel wire armour, so they are well adapted to underground use in industrial applications, in moist areas.

### STANDARDS

BS 6346

### FIRE PERFORMANCE

Flame Retardant	IEC60332 part 1, BS4066 part 1
-----------------	--------------------------------

### VOLTAGE RATING

1900/3300V

### CABLE CONSTRUCTION

Conductor: Copper conductor, round stranded Class 2 to BS 6460, IEC 60228

Insulation: PVC (Polyvinyl Chloride) type T11

Filler (optional): PVC or Polypropylene yarn

Binder Tape (optional): Polyester (Mylar) tape

Inner Sheath/ Bedding: PVC (Polyvinyl Chloride)

Armour: AWA (Aluminum Wire Armour)

Outer Sheath: PVC (Polyvinyl Chloride), type TM1

### COLOUR CODE

Insulation: Brown.

### PHYSICAL AND THERMAL PROPERTIES

Temperature rating: -20°C to +60°C

Bending radius:

Single core: 10 x overall diameter



**Caledonian**

BS 6346 Cables

[www.caledonian-cables.com](http://www.caledonian-cables.com)

[marketing@caledonian-cables.com](mailto:marketing@caledonian-cables.com)

Multicores: 8 x overall diameter

#### DIMENSION AND PARAMETERS

No. of Cores × Cross- sectional Area	No. and Dia. of Wires	Nominal Insulation Thickness	Nominal Bedding Thickness	Nominal Sheath Thickness	Nominal Aluminum Wire Armour Diameter	Approx. Overall Diameter	Approx. Weight
No. × mm <sup>2</sup>	no./mm	mm	mm	mm	mm	mm	kg/km
1x400	61/2.85	2.6	1.2	2.1	2	42	4655