



Caledonian


IEC60092 Offshore & Marine Cables

www.caledonian-cables.com

marketing@caledonian-cables.com

BOI/BOU (MFX300) 0.6/1 kV Mica Tape + XLPE Insulated, LSOH (SHF1) Sheathed,Armoured Fire Resistant Power & Control Cables (Single Core)

MFX300-1mRMZ1-R-1C50



APPLICATIONS

These armoured fire resistant cables are used on board of ships in all locations for fixed installations where cable protection is required. These cables are fire resistant, flame retardant, low smoke & halogen free.

STANDARDS

IEC 60092-350/353/360

IEC 60331-21

IEC 60332-1

IEC 60332-3-22

IEC 60754-1/2

IEC 61034

CABLE CONSTRUCTION

Conductors: Class 2 stranded copper conductor. Class 5 stranded conductors can be offered upon request.

Insulation: Mica tape + XLPE.

Armour: Copper wire braid.

Outer Sheath: LSOH (SHF1). SHF2 can be offered upon request.

COLOUR CODE

Single core: Black.

PHYSICAL AND THERMAL PROPERTIES

Bending Radius for Fixed Installations: 6×OD

Temperature Range: -30°C ~ +80°C

DIMENSION AND PARAMETERS

Caledonian Cable Code	No. of Cores × Cross-sectional Area	Nominal Insulation Thickness	Nominal Sheath Thickness	Nom. Overall Diameter	Approx. Weight
	No.×mm ²	mm	mm	mm	kg/km



Caledonian

IEC60092 Offshore & Marine Cables

www.caledonian-cables.com

marketing@caledonian-cables.com

MFX300-1mRMZ1- R-1C50	1×50	1.0	1.3	15.8	720
--------------------------	------	-----	-----	------	-----