



Caledonian


IEC60092 Offshore & Marine Cables

www.caledonian-cables.com

marketing@caledonian-cables.com

RFOI /RFOU (MTX400) 0.6/1 kV HEPR Insulated, LSOH (SHF1) Sheathed, Screened Flame Retardant Power & Control Cables((3 Cores))

MTX400-1G7MZ1-R-3C2.5



APPLICATIONS

These cables are used for fixed installations on ships and offshore units in all locations and on open deck. The good screening qualities of the copper braid also reduce radio interference and electrical influences to electronics installations. These cables are flame retardant, low smoke & halogen free.

STANDARDS

- DIN 89160/98
- IEC 60092-353
- IEC 60332-1
- IEC 60332-3-22
- IEC 60754-1/2
- IEC 61034

CABLE CONSTRUCTION

- Conductors: Class 2 stranded copper conductor.
- Insulation: HEPR.
- Inner Covering: Lapping or extruded filler.
- Overall Screen: Copper wire braid.
- #Outer Sheath: LSOH (SHF1).

COLOUR CODE

Three cores: Black, Blue, Brown.

PHYSICAL AND THERMAL PROPERTIES

- Bending Radius for Fixed Installations: 6×OD
- Temperature Range: -20°C ~ +75°C

DIMENSION AND PARAMETERS

Caledonian Cable Code	No. of Cores × Cross-sectional Area	Nominal Insulation Thickness	Nominal Sheath Thickness	Nom. Overall Diameter	Approx. Weight
	No. ×mm ²	mm	mm	mm	kg/km



Caledonian

IEC60092 Offshore & Marine Cables

www.caledonian-cables.com

marketing@caledonian-cables.com

MTX400-1G7MZ1- R-3C2.5	3×2.5	0.7	1.2	12.8	260
---------------------------	-------	-----	-----	------	-----