



Caledonian


EN 50306 Rolling Stock Cables

www.caledonian-cables.com

marketing@caledonian-cables.com

FIREROL Thin Wall Multicore Overall Screened Cables with Exposed

EN 50306-4 (FRL-TW-05M-ESW-OS)



APPLICATIONS

- Used as signal and control cable for protected installations inside and outside of rail and transport vehicles, where space and weight are an important factor.
- Used in cable harnesses, switchboards and control panels, driver desks etc.

VOLTAGE RATING

300/500 V

CABLE CONSTRUCTION

Conductor:Tinned annealed copper wires as defined in EN 50306-2

Insulation:LSZH special compound

Overall Screen:Tinned annealed copper wires

Outer Sheath:LSZH special compound as defined in EN 50264-1 (S2, EM 101 - EM 104)

MECHANICAL PROPERTIES

Max. Conductor Temperature:90 °C/105 °C (fixed installation)

Min. Permissible Ambient Temperature:-25 °C/-40 °C (fixed installation)

Bending Radius: 10 x Overall Diameter

CHEMICAL AND ENVIRONMENTAL PROPERTIES

| | |
|------------------------|---|
| EN 60684-2 | No fluorine |
| EN 50305; EN 60811-2-1 | Resistance to mineral oil & fuel oil, acid & alkali |
| EN 50305 | Resistance to ozone |

FIRE PERFORMANCE FOR ROLLING STOCK APPLICATION

| | |
|-------------|--|
| EN 50306-2 | Hazard levels HL1, HL2, HL3 |
| DIN 5510-2 | Protection level 1/2/3/4 |
| BS 6853 | Interior use 1a, 1b, II; Exterior use 1a, 1b, II |
| NF F 16-101 | F0 |
| EN45545-2 | R15 Interior/ R16 Exterior HL1, HL2, HL3 |

FIRE PERFORMANCE IN GENERAL



Caledonian

EN 50306 Rolling Stock Cables


www.caledonian-cables.com

marketing@caledonian-cables.com

| | |
|---|---|
| EN 50265-2-1; IEC 60332-1-2; NF C 32-070 2.1 (C2) | Vertical flame propagation for a single insulated wire or cable |
| EN 50266-2-4 + EN 50305; IEC 60332-3-24;NF C 32-070 2.2 (C1); VDE 0472 Teil 804 | Vertical flame spread of vertically mounted bunched wires or cables |
| EN 50268-2; IEC 61034-2; NF C 32-073 ;NF C 20-902; NF F 16 101; VDE 0472 Teil 816 | Low Smoke Emission |
| EN 50267-2-1; IEC 60754-1; NF C 32-074;NF C 20-454; VDE 0472 Teil 815 | Halogen Free |
| EN 50267-2-2/3; IEC 60754-2; NF C 32-074;NF C 20-453; VDE 0472 Teil 813 | Low Corrosivity (Acidity & Conductivity) |
| EN 50305; NF X 70-100; NF F 63 808; TM1-04; BS6853 | Low Toxicity |
| NF F 63 808; BS6853; NF F 16 101 | Smoke Index |
| EN45545-2 | Requirement for fire behavior of materials & components R15/R16 |

DIMENSION AND PARAMETERS


| No. of Cores × Cross-sectional Area | Min. Mean Thickness of Sheath | Overall Diameter (min.) | Overall Diameter (max.) | Approx. Weight |
|-------------------------------------|-------------------------------|-------------------------|-------------------------|----------------|
| No. ×mm ² | mm | mm | mm | kg/km |
| 3x2.5 | 1.0 | 8.6 | 9.8 | 150 |



Abrasion Retardant



Acid & Alkaline Resistant



Cold Resistant



Corona Resistant



Fire Retardant
NF C32-070-2-2(C1)
IEC60332-3-24/EN50266-2-4



Flame Retardant
NF C32-070-2-1(C2)
IEC60332-1-1/EN50265-2-1



Highly Flexible



IRM 902
Mineral Oil Resistant



IRM 903
Fuel Oil Resistant




Low Corrosivity
IEC60754-2/EN50267-2-2/3
NF C32-074/NF C20-453




Low Smoke Emission
IEC 61034-2 / EN 50268-2
NF C32-073/NF C 20-902




Low Toxicity
EN 50305; NF X70-100/NF
F63 808/TM1-04/BS 6853



Ozone Resistant



Resistance To
Soldering Heat



UV Resistant



Zero Halogen
IEC 60754-1/EN 50267-2-1
NF C20-454