



Caledonian



BS 5467 Cables

www.caledonian-cables.com

marketing@caledonian-cables.com

BS 5467 Armoured Power Cables, 1900/3300V

Single-core 1900/3300V cables with solid aluminum conductor
1C300



APPLICATIONS

These cables are used for power and control circuits, they can offer excellent protection through the use of a heavy galvanized steel wire armour. The GSWA makes them suitable for use inside and outside buildings or for direct burial in the ground.

STANDARDS

BS 5467

FIRE PERFORMANCE

| | |
|-----------------|-----------------|
| Flame Retardant | BS EN 60332-1-2 |
|-----------------|-----------------|

VOLTAGE RATING

1900/3300V

CABLE CONSTRUCTION

Conductor: Solid Aluminum conductor, circular, Class 1 to BS EN60228.

Insulation: XLPE (Cross-Linked Polyethylene) Type GP 8 conforming to BS 7655-1.3 or type GP6 conforming to BS 7655-1.2.

Bedding: The bedding shall consist of an extruded layer of polymeric material consistent with the operating temperature of the cable.

Armour: AWA (Aluminum Wire Armour).

Outer Sheath: Extruded PVC, type 9 specified in BS7655-4.2.

COLOUR CODE

Insulation: Brown.

PHYSICAL AND THERMAL PROPERTIES

Temperature rating 0°C to +90°C

Bending radius: 1.5mm² to 16mm²: 6 x overall diameter

25mm² and above: 8 x overall diameter



Caledonian

BS 5467 Cables

www.caledonian-cables.com

marketing@caledonian-cables.com

DIMENSION AND PARAMETERS

| No. of Cores × Cross- sectional Area | Nominal Insulation Thickness | Nominal Bedding Thickness | Nominal Sheath Thickness | Nominal Aluminum Wire Armour Diameter | Approx. Overall Diameter | Approx. Weight |
|--|------------------------------------|---------------------------------|--------------------------------|--|--------------------------------|-------------------|
| No.×mm ² | mm | mm | mm | mm | mm | kg/km |
| 1x300 | 2 | 1 | 1.9 | 1.6 | 32.8 | 1900 |