



# Caledonian



BS 7211 LSOH Sheathed Cables

www.caledonian-cables.com

marketing@caledonian-cables.com

## Thermosetting insulated, twin circular sheathed cables

4C6



## APPLICATIONS

These cables are designed for fixed wiring purposes in domestic and industrial power/lighting applications. Can be used in trunking or conduit, or may be surface mounted when used for earthing. and generally in areas (such as public and government buildings) where smoke and toxic fumes may cause a threat to life and equipment. The cables produce no corrosive gasses when burnt which is particularly important where electronic equipment is installed.

## FIRE PERFORMANCE

Flame retardant	IEC 60332-1
Smoke density	EN 50268 / IEC 61034
Corrosiveness of combustion gases	EN 50267-2-2, IEC 60754-2
Flame test: flame-retardant	EN 50265-2-1, IEC 60332-1

## CABLE CONSTRUCTION

- Fine bare copper strands
- Strands to IEC 60228 Cl-2
- Thermosetting core insulation type EI5 or GP 8
- The cores shall be twisted together. A centre filler may be used.
- The twisted core shall be covered by an extruded inner covering or separating tape
- LSOH sheath, type LTS 4

## COLOUR CODE

Insulation Colour

4-core: blue, brown, black and grey

## Electrical Properties

- Working voltage: 450/750v
- Test voltage: 2500 volts
- Flexing bending radius: 15 x Ø
- Static bending radius: 10 x Ø



# Caledonian

BS 7211 LSOH Sheathed Cables

[www.caledonian-cables.com](http://www.caledonian-cables.com)

[marketing@caledonian-cables.com](mailto:marketing@caledonian-cables.com)

- Flexing temperature: -25° C to +90° C
- Short circuit temperature: +250° C
- Insulation resistance: 10 MΩ x km

## DIMENSION AND PARAMETERS

No. of Cores × Cross- sectional Area	AWG Size	Nominal Insulation Thickness	Nominal Thickness of Inner Covering	Nominal Sheath Thickness	Nom. Overall Diameter	Approx. Weight	Min. Insulation Resistance at 90 °C
No. × mm <sup>2</sup>		mm	mm	mm	mm	kg/km	MΩ × km
4x6	10(7/18)	0.7	0.4	1.4	13.8-16.7	490	0.0059